DNIT for Repair of SSE and Staff Washroom at 132 KV S/S Mammon .

s	No		FAnti-skid floor tiles 10mm thick in flooring skirting and ido in 12.5mm thick cement plaster 1:3 in base and inted with white cement slurry in joints including corners and beading		Unit	C	CSR Ref	Total Rate		Rate to be quoted by contractor
	7 1	ismantling ement			Sqm					
	2	dado in 12. ointed with angles and			Sqm		14.72	557.22		
	3	conforming	and fixing 1st quality ceramic glazed wall tiles g to size 300x450 mm assteps and dados over ck bed of cement Mortar 1:4 approved by in-Charge	34.20	Sqm		14.127	677.74		
	4		hick cement plaster 1:4	34.20	Sqm		15.9	136.67		
	5	not to be	g Doors and Windows (Steel or wood) with ts by making recesses in walls when the wall is dismantled					2		4
			Door of area 3 sqm and below	5	No		8.26(a)	199.11		
			Window of area 3 sqm and below	1	No		8.26(b)	126.79		
		tubular s sections approve	g and fixing aluminium work for doors, windows, ors and partitions with extruded built up standard sections/appropriate z sections and other sindal, Hindalco, Mahavir or equivalent make addy for the sections and other sections.	71.09	KG		17.45(a)	314.29	43	
		fittings neopre	tters of doors, windows & ventilators including and and fixing hinges/pivots and labour for fixing of wherever required including the cost of PVC Plug are gaster required.	48.47	· Kg		17.45(b)	328.57		·
		board fi board is shutten	ng and fixing 12mm thick prelaminated particle lat pressed three layer or graded wood particle in paneling fixed in aluminium doors, windows is and partition frames with C.P. brass / stainless	9.21	sqr	n	17.46(i)	853.57		
		fittings	Aluminium fittings complete for doors, windows tower bolts, handless and screw etc. for these (Excluding sliding bolt)	15.37	sqı	n	17.23(ii)	99.11		
	1	ventilate neoprer	ng and fixing glazing in aluminium door, window, or shutters and partitions etc. with PVC Plug/ ne gasket etc. complete	0.98	sq	m	17.47(i)	924.1071	4	
	1	complet	e gauge 12x12 size in aluminium section etc. le as per NS item	0.98	sq	m	NS	450.39		
	12		ng and laying 3 layer PPR pipe of 25 mm o/d	40.00	m	tr :	28.39A(a)	171.28		
	13	Providin	g and laying 3 layer PPR pipe of 20 mm o/d	15.00	m	tr	28.39A(a)	135.48	\dashv	
<u> </u>	14	make on	Fixing General purpose tube fitting of cropmtor wall model no. DIL B124 14 EB9 (1*36 WATT)	4.00	r	0	NS	410.00		•
	15	Pattern) of ground of complete	g, fixing and jointing gun-metal peet valves (Hea with hand wheels, on G.I. Pipe lines laid in the r inside buildings including all carriages .20mm i/d G.I union	2	ı	10	28.43(b)	793.77	,	
		water clos Engineer- cistern sup lia	and fixing in position Chinaware European typ set P trap or S trap (to the approval of the in-charge) suite-consisting of 10 ltr. PVC flush oported on angle iron bracket, short bend 32 n	ing 2		No	30.4	4267.8	36	
	' c	.P. Brass		Vith 2		no	30.8(8	425	5	
	tap complete.Size 550 mm x 400 mm			s 2		No	30.32	(ii) 322	6.79	
19	Providing & fixing in position best Indian make (to be approval of the Engineer-incharge) vitreous Chinware white flat back or angular lipped front urinal size 440 x 31 x 265 mm C.P. brass flexible tube connection 450 mm		315	2	No	30.	15 26	66.96		

			·			l	1
20	bra	viding & Fixing in postion 15 mm i/d bib cock of cp las without flange (as approved by the Engineer-inarge).	5	No	30.65(a)(ii)	818.75	
2	Pr IS	roviding, Stringing out U.P.V.C. Pipes casting asper 5:15328-2003 class-SN-8 along the trenches and laying the same in Trenches to correct alignment and gradients, autting and jointing including cost of specials complete as over specifications.110mm o/d pipe	30	MTR	30.74(iii)b	265.88	
	22	Providing & Fixing in postion stop cock / Angle valve cp brass(as approved by the Engineer- incharge) C.P.brass 15mm stop cock Male and female end	5	No	30.66(a)	716.96	
	23	Providing & Fixing in position best indian make bevelled edge 5mm thick mirror mounted on 4mm thick Cardboard sheet ground fixed in position by means of 4 nos. chromium plated brass screws and washers .Size 600mmx450mm	2	No	30.61(a)	1070.53	
	24	Providing and fixing in position towel rails of approved make including cutting and making good the walls etc CP brass Rails size 15mm dia 600mm long	2	no	30.58(a)	1374.11	
	24	with H.C.I. grating and cast iron cover weighing approximately 7.26 kg. and frame clear opening 300mm x 300mm and out of side size 330mm x300mm.	2	No	30.99(a)	1635.71	
	25	approved brand	5	No	30.80	98.80	
	26	and manufacturer to give an even shade (two coats)	39.70	Sqm	16.63	79.46	
	27	cement based wall putty by applying two coats to get	9.92475	sqm	16.65	71.43	
	28	item30.97A(i)	500.00	ltr	30.97A(i)	9.64	
	29 30	per NS item	2.00	no	NS	1772.00	
		Providing and fixing in position cp brass soap dish	2.00	nos	1 20.00		
ļ	32	Extra carriage for fine sand	1.28	Cum	30.60	752.68	
1	33	Extra Carriage for cement	0.5	_	Annex	256.80	
1	Note			MT	Annex	529 51	

Notes: -

- These rates are through rates exclusive of Cement & Steel that shall be issued by PSTCL from jamsher/ablowal store.
- PWD/ PSTCL specifications will be followed for all the above items, for which ref. to CSR items and NS items is given.
- For any NS item, which is not covered in DNIT, shall be allowed on the same pattern of AOR with the prior approval of Er – in – Charge.
- 4. GST will be applicable as per Govt. norms and will be paid extra.
- Rates of taxes and duties if any applicable must be mentioned clearly otherwise maximum rate shall be taken into account for evaluation purposes.

Signature of vendor

