5 No.	Qty. 84.00	Description of Item  Scraping of Cement Plaster	Units	CSR Ref	CSR/ Deptt Rates	Rate to be quoted by contractor
1		12.5mm thick cement plaster 1:4 parapet	Sqm	8.31(c)	32.14	Contractor
2		piastei	Sqm	15.9	136.67	
3 (a)	2	Removing Doors and Windows (Steel or wood) with chowkhats by making recesses in walls when the wall is not to be dismantled (Door of area 3sqm or below)	No	8.26(a)	199.11	
3(b)	3.00	Removing Doors and Windows (Steel or wood) with chowkhats by making recesses in walls when the wall is not to be dismantled (Window of area 3sqm or below)		8.26(b)	126.79	
	29.66	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate z sections and other sectionslindal, Hindalco, Mahavir or equivalent make approved by Engineer in Charge	КG	17.45(a)	314.28	
5	23.54	For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and labour for fixing of fittings wherever required including the cost of PVC Plug / neoprene gasket required	. Kø	17.45(b)	328.57	
6	1.45	Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or graded wood particle board in paneling fixed in aluminium doors, windows shutters and partition frames with C.P brass / stainless steel screws etc. complete	s sqm	17.46(i)	853.57	
7	18.98	Cost of Aluminium fittings complete fo doors, windows such as tower bolts handless and screw etc. for these fitting (Excluding sliding bolt)	s sqm	17.23(ii)	99.11	
8	3.26	Providing and fixing glazing in aluminium door, window, ventilator shutters an partitions etc. with PVC Plug/ neopren gasket etc. complete	d sqm e	17.47(i)	924.11	
9	50	Supply and erection of PVC insulated single core FRLS Copper conductor cable is marked left bare in pipe or casing of suitable size excluding the cost of supple and erection of pipe or casing. PV Insulated copper conductor single core FRL cable (ISI marked) overall 2.5 sq.mm 1100volts grade	SI of dy C Rm S	34.09(iv)	31.34	
10	10	Providing and laying, jointing fixing ar testing G.I. Pipe lines B-Class including co of specials such as tees, bends, socket elbows etc. testing, cutting, threading inside building complete 15mm i/d	st s, MTR de	28.36(a)	184.94	
11	2	Providing, fixing and jointing G.I. Unk complete on all respect 15mm i/d G.I. unk		28.40(a)	81.25	-
12	359.31	Wall painting with plastic emulsion paint approved brand and manufacturer to gi an even shade (two coats)	of ve Sqm	16.63	79.46	

-				Cam	8.31 a	6.25	
	13	215.58	Scraping of white wash and color wash	Sqm			14
	14	89.83	Preparation of plastered or concrete surface for painting (incl. sand papering the surface) using ready mixed cement based wall putty by applying two coats to get required finish	Sqm	16.65	71.43	
	15	42.9	Finishing walls with acrylic smooth exterior paint of required shade with two coats applied @ 1.67 litre/10sqm over and including base coat of water proofing Cement Paint applied @ 2.20 Kg/10 sqm	sqm	16.59	107.14	
	16	43.11	Painting one coat with synthetic enamel paint in all shades on old wood work or metallic or plastered or concrete surfaces to give an even shade including rubbing down	sqm	16.19	32.14	
	17	1.95	old paint. Dismantling cement conglomerate floors (25mm to 50mm) thick without concrete	Sqm	8.16	97.32	
	18	1.95	Conglomerate floor 25mm thick cement concrete topping 1:2:4 using mechanical	Sqm	14.5	169.72	
	19	1.95	mixer for mixing of material  P/F Anti-skid floor tiles 10mm thick in flooring skirting and dado in 12.5mm thick cement plaster 1:3 in base and jointed with whitecement slurry in joints including corners angles and beading	Sqm	14.72	557.22	
	20	10.08	Providing and fixing 1st quality ceramic glazed wall tiles conforming to fsize 450 x 310 mm as steps and dados over 12 mm thick bed of cement Mortar 1:4 approved by Engineer-in-Charge in	Sqm	14.127	677.74	
	21	2	Providing and fixing hydraulic door closer ISI mark with necessary screw etc. complete I.S.I Designation No. III (size of door 851mm	each	17.43 c	1169.64	
		6.48	to 1000mm)  Renewing glass panes with putty and nails	sqm	31.5 A	203.57	
	22	0.83	wherever necessary  First class burnt brick work laid in cement sand mortar 1:5 in first storey upto 4 metres above plinth level	cum	11.6	4211.42	
	24	1	Providing and fixing in position Chinaware European Type water closet P trap or S trap (to the approval of the engineer-in-charge) suite-consisting of 10ltr. PVC flushing cistern supported on angle iron bracket, short bend 32mm dia	No.	30.4	4267.86	
	25	1	Providing and fixing jet spray with 2'-6" long PVC pipe. With C.P.Brass nut	No.	30.8(a)	425.00	
	26	1	Providing and fixing in position vitreous chinaware white lavatory suites of approved make (to the approval of Engineer-in charge) consisting of C.P. brass waste 32mm dia with one C.P. brass pillar tap including Rack Bolt Screw Pair 115mm long complete in all respect. Size 550 mm x 400 mm x 815 mm	*	30.32(ii)	3226.79	
	27	1	Providing & fixing in position vitreous Chinware white Indian make flat back or angular lipped front small urinals size 265x315x440mm approved make (to the approval of the Engineer-in-charge) with C.P. brass tube connection 300 mm long complete in all respect.	No.	30.15	2666.96	

	The second second second second					
28	2	Providing & Fixing in postion 15 mm I/d bib cock of approved make (to the approval of Engineer-in-charge )complete in all respect.  C.P. brass Bib cock foam flow without flange	No.	30.65(a)(ii)	818.75	
29	2	Providing & Fixing in postion stop cock / Angle valve of approved make (to the approval of Engineer-in-charge ) complete in all respect. C.P.brass 15mm stop cock Male and female end	No.	30.66(a)	716.96	
30	1	Providing & Fixing in position 5mm thick bevelled edge mirror of superior glass (of approved make) complete with 4mm thick hard board backing fixed in with rawl plugs 50mm, C.P. brass screws and washers and S/S Studs on top complete in all respect (as required by the Engineer-in- Charge) Size 600mmx450mm	No.	30.61(a)	1070.53	
31	1	Providing and fixing in position towel rails of approved make including cutting and making good the walls etc CP brass Rails size 15mm dia 600mm long		30.58(a)	1374.11	
32	10	Providing and fixing rail 1.90cm chrome- plated with end bracket including sockets and brackets	Rmt	31.33	268.75	
33	2	Providing and fixing in position S.S. grating with frame of approved brand	No.	30.80	98.80	
34	6	Supplying and fixing general purpose tube fitting of Crompton make 1x28W as per NS item	No.	NS	410.00	
35	-20.00	Less iron scrap	kg		20.00	
36	-40.00	Less wooden scrap	kg		6.00	
37		Extra carriage and difference of rates				
(i)	0.65	Cement	MT	Annex	261.40	
(ii)	1.75	Fine sand	cum			
(iii)	0.02	coarse sand	cum			
(iv)	0.02	Crusher 11.2mm	cum	- AF		
(v)	0.02	Crusher 13.2mm	cum			
(vi)	0.40	Bricks	No.	Anne	042.79	

## Notes: -

- 1. These rates are through rates exclusive of Cement & Steel that shall be issued by PSTCL from jamsher/ablowal store.
- 2. PWD/ PSTCL specifications will be followed for all the above items, for which ref. to CSR items and NS items is given.
- 3. For any NS item, which is not covered in DNIT, shall be allowed on the same pattern of AOR with the prior approval of Er in Charge.
- 4. GST will be applicable as per Govt. norms and will be paid extra.
- Rates of taxes and duties if any applicable must be mentioned clearly otherwise maximum rate shall be taken into account for evaluation purposes.

Signature of vendor