

**DNIT for Repair and maintenance of roof and bathrooms at 220 KV S/S Mandi
Gobindgarh-3 Tooran**

S No	Qty	Description of an item	Unit	CSR Ref	CSR/Dept Rates	Rates to be quoted by contractor
1	101.25	Regrading terracing of mud plaster covered with tiles or bricks in cement by dismantling tiles or bricks, removing mud plaster, preparing the surface of mud plaster to proper, slope, relaying mud plaster Gobri leaping and tiles or bricks grouted in cement mortar 1:3 (1 cement and 3 fine sand)	sqm	31.11	348.67	
2	31.5	Cement concrete 1:2:4 gola 10cm x 10cm concave quadrant	rmt	13.55	44.30	
3	0.937	Replacement of worn out tiles with new one	1000 no	NS	5777.00	
4	101.25	Providing and fixing Polythene sheet	Sqm	NS	20.00	
5	52.5	Scraping of Cement Plaster	sqm	8.31 c	32.14	
6	52.5	12.5mm thick cement plaster 1:4	sqm	15.9	136.67	
7	500	Providing & fixing in position on terrace (at all floor levels) HDPE tank cover for water storage tanks of approved make (to the approval of Engineer -in-charge) complete in all respect. Triple layer tank	Ltrs	30.97 b i	9.64	
8	27	Providing and laying four courses of water proofing treatment with bitumen felt over roofs consisting of first and third courses of blown type bitumen grade 85/25 applied hot at 1.20 Kg. Per sqm of area for each course second course on roofing felt type 3 grade-1 (Hession base self finished bitumen felt) and fourth and final course of stone grit 6mm and down size or pea sizes grit spread at 0.006 cum per Sqm including preparation of surface complete.	Sqm	13.56	286.61	
9	3	Providing & Fixing in position 15 mm i/d bib cock of cp brass without flange (as approved by the Engineer-in-charge).	Each	30.65(a)(ii)	818.75	
10	3	Providing & Fixing in position stop cock / Angle valve cp brass (as approved by the Engineer-in-charge) C.P. brass 15mm stop cock Male and female end	Each	30.66(a)	716.96	
11	3	P&F In position PVC flexible tube connection of approved make PVC tube connection of size 15 mm X 450 mm with CP Brass nut	Each	30.72 b	162.50	

12	1	Providing and fixing in position Chinaware European type water closet P trap or S trap (to the approval of the Engineer-in-charge) suite-consisting of 10 ltr. PVC flushing cistern supported on angle iron bracket, short bend 32 mm dia	Each	30.4	4267.86	
13	1	Providing and fixing in position best Indian make white ordinary lavatory suites consisting of C.P. brass waste 32mm dia, pair of angle iron bracket with one C.P. brass tap complete. Size 550 mm x 400 mm	Each	30.32 ii	3226.79	
14		Extra Carriage and difference of material rates				
A	0.6	cement	MT	Annex	256.7	
B	1.34	fine sand	Cum	Annex	256.8	
C	0.11	coarse sand	Cum	Annex	294.93	
D	0.11	crusher 11.2 mm	Cum	Annex	417.74	
E	0.11	crusher 13.2 mm	Cum	Annex	408.65	

Notes: -

- 1 These rates are through rates exclusive of Cement & Steel that shall be issued by PSTCL from jamsher/ablowal store(As per Availability).
- 2 Any error regarding description,reference to CSR, Quantity, rate, premium ,unit, calculations omission,addition will be corrected at any stage as per CSR,AOR,Specification and drawings and no claim whatsoever shall be entertained on this account.
- 3 PWD/ PSTCL specifications will be followed for all the above items, for which ref. to CSR items and NS items is given.
- 4 For any NS item, which is not covered in DNIT, shall be allowed on the same pattern of AOR with the prior approval of Er – in – Charge.
- 5 GST will be applicable as per Govt. norms and will be paid extra.
- 6 Rates of taxes and duties if any applicable must be mentioned clearly otherwise maximum rate shall be taken into account for evaluation purposes.
- 7 At the time of final billing, the merit position w.r.t actual work done shall be prepared again and total payment to be paid to the contractor shall be restricted as per cost percentage w.r.t. departmental rates of L-1 in revised comparative statement and approved comparative statement . In case if the merit position of L-1 contractor changes, the total payment to contractor will be restricted to L-1 Cost of revised comparative statement.

Signature of vendor